




























STANDARD BOLT

HOW TO DETERMINE BOLT STRENGTH

Bolt Type

| Hexagon Head Bolt | | Stud Bolt | Weld Bolt | Class |
|---|---|--|---|-------|
| Normal Recess Bolt | Deep Recess Bolt | | | |
|  | No Mark  | No Mark  |  | 4T |
|   |  | | | 5T |
|  | w/ Washer  | w/ Washer  |  | 6T |
|   |   | | | 7T |
|  |  |   | | 8T |
|  |  | | | 9T |
|  |   | | | 10T |
|  |   | | | 11T |

SS














SPECIFIED TORQUE FOR STANDARD BOLTS

| Class | Diameter (mm) | Pitch (mm) | Specified torque | | | | | |
|-------|------------------|---------------|-------------------|--------|------------|---------------------|--------|------------|
| | | | Hexagon head bolt | | | Hexagon flange bolt | | |
| | | | N*m | kgf*cm | ft.*lbf | N*m | kgf*cm | ft.*lbf |
| 4T | 6 | 1 | 5 | 55 | 48 in.*lbf | 6 | 60 | 52 in.*lbf |
| | 8 | 1.25 | 12.5 | 130 | 9 | 14 | 145 | 10 |
| | 10 | 1.25 | 26 | 260 | 19 | 29 | 290 | 21 |
| | 12 | 1.25 | 47 | 480 | 35 | 53 | 540 | 39 |
| | 14 | 1.5 | 74 | 760 | 55 | 84 | 850 | 61 |
| | 16 | 1.5 | 115 | 1,150 | 83 | - | - | - |
| 5T | 6 | 1 | 6.5 | 65 | 56 in.*lbf | 7.5 | 75 | 65 in.*lbf |
| | 8 | 1.25 | 15.5 | 160 | 12 | 17.5 | 175 | 13 |
| | 10 | 1.25 | 32 | 330 | 24 | 36 | 360 | 26 |
| | 12 | 1.25 | 59 | 600 | 43 | 65 | 670 | 48 |
| | 14 | 1.5 | 91 | 930 | 67 | 100 | 1,050 | 76 |
| | 16 | 1.5 | 140 | 1,400 | 101 | - | - | - |
| 6T | 6 | 1 | 8 | 80 | 69 in.*lbf | 9 | 90 | 78 in.*lbf |
| | 8 | 1.25 | 19 | 195 | 14 | 21 | 210 | 15 |
| | 10 | 1.25 | 39 | 400 | 29 | 44 | 440 | 32 |
| | 12 | 1.25 | 71 | 730 | 53 | 80 | 810 | 59 |
| | 14 | 1.5 | 110 | 1,100 | 80 | 125 | 1,250 | 90 |
| | 16 | 1.5 | 170 | 1,750 | 127 | - | - | - |
| 7T | 6 | 1 | 10.5 | 110 | 8 | 12 | 120 | 9 |
| | 8 | 1.25 | 25 | 260 | 19 | 28 | 290 | 21 |
| | 10 | 1.25 | 52 | 530 | 38 | 58 | 590 | 43 |
| | 12 | 1.25 | 95 | 970 | 70 | 105 | 1,050 | 76 |
| | 14 | 1.5 | 145 | 1,500 | 108 | 165 | 1,700 | 123 |
| | 16 | 1.5 | 230 | 2,300 | 166 | - | - | - |
| 8T | 8 | 1.25 | 29 | 300 | 22 | 33 | 330 | 24 |
| | 10 | 1.25 | 61 | 620 | 45 | 68 | 690 | 50 |
| | 12 | 1.25 | 110 | 1,100 | 80 | 120 | 1,250 | 90 |
| 9T | 8 | 1.25 | 34 | 340 | 25 | 37 | 380 | 27 |
| | 10 | 1.25 | 70 | 710 | 51 | 78 | 790 | 57 |
| | 12 | 1.25 | 125 | 1,300 | 94 | 140 | 1,450 | 105 |
| 10T | 8 | 1.25 | 38 | 390 | 28 | 42 | 430 | 31 |
| | 10 | 1.25 | 78 | 800 | 58 | 88 | 890 | 64 |
| | 12 | 1.25 | 140 | 1,450 | 105 | 155 | 1,600 | 116 |
| 11T | 8 | 1.25 | 42 | 430 | 31 | 47 | 480 | 35 |
| | 10 | 1.25 | 87 | 890 | 64 | 97 | 990 | 72 |
| | 12 | 1.25 | 155 | 1,600 | 116 | 175 | 1,800 | 130 |

SS

HOW TO DETERMINE NUT STRENGTH

Nut Type

| Present Standard Hexagon Nut | Old Standard Hexagon Nut | | Class |
|--|--|---|----------|
| | Cold Forging Nut | Cutting Processed Nut | |
| No Mark  | | | 4N |
| No Mark (w/ Washer)  | No Mark (w/ Washer)  | No Mark  | 5N (4T) |
|  | | | 6N |
| |  |  | 7N (5T) |
|  | | | 8N |
|  |  | No Mark  | 10N (7T) |
|  | | | 11N |
|  | | | 12N |

HINT:

- *: Nut with 1 or more marks on one side surface of the nut.
- Use a nut with the same nut strength classification number (or greater) as the bolt strength classification number when tightening parts with a bolt and nut.

Example:

- Bolt = 4T
- Nut = 4N or more